

DHI-ISC-ETA1-R122

AM Label



- Easy to use, suitable for most commodities.
- Small in size, able to provide concealed protection.
- Better adhesion and no need to worry about the backing adhesive coming off.
- Adopts self-adhesive process, which has good adhesion and less residual adhesive.

Introduction

The AM Label can be used together with the Acousto-Magnetic antenna to effectively prevent the theft from the goods.

Features

Suitable for Abundant Products

Apply to any flat non-metallic surface, easy to use.

Extremely Low Cost

Disposable products, needs to be demagnetized after it's sold.

Good Detection Effect

High detection rate, good anti-theft effect.

Scene

The label can be fixed on various goods.

Technical Specification

Performance

Model	DHI-ISC-ETA1-R122
Technology	Acousto-Magnetic (AM)
Detection Frequency	58 kHz ± 0.5 kHz
AM Antenna Detection Distance	≤ 0.8 m (Based on system performance)
Shell Material	Polyethylene Terephthalate
Marking	Barcode
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

General

Backing Adhesive	Yes
Color	White
Vibration Chips	3 Pcs
Product Dimensions	60 mm × 39 mm (2.36" × 1.54")
Carton Dimension	380 mm × 200 mm × 435 mm (14.96" × 7.87" × 17.13")
Packaging	5,000 AM Labels per carton
Net Weight	4.65 kg (10.25 lb)
Carton Weight	5.05 kg (11.13 lb)
Sales Unit	Carton

Environmental Constraints

Temperature	0 °C to 50 °C (32 °F to 122 °F)
Humidity	20 % - 60 % (RH)

Ordering Information

Type	Model	Description
AM Label	DHI-ISC-ETA1-R122	AM Label R122